

SCHEDULE OF ARTICLES

Reversible Duplex-Filter Type DF 40

page 1 / 1

Duplex-Filter with ball valve reversing unit in welded steel / stainless steel design

medium	:
temperature	:	°C
filter lock	:	with screws
main connection flanges according to DIN PN 16 superimposed - at same levels	:	mm
circulatory capacity	:	m ³ /h
filter-element	:	basket-type strainer / ring-type strainer
fineness of filtration	:	µm
filter area	:	cm ²
working pressure	:	bar
design pressure	:	bar 10
pressure loss with clean filter approx.	:	bar 0,15
max. admissible pressure loss approx.	:	bar 1,5
weight empty	:	kg

materials

filter housing	:	steel / stainless steel 1.4571
cover seal	:	NBR
filter insert, basket-type / ring-type strainer of perforated sheet	:	stainless steel 1.4301
covered with gauze	:	stainless steel 1.4401
reversing with ball valve	:	steel / stainless steel
<u>differential pressure switch</u>	:	with an electrical switching contact

optical-electrical, mounted at the filter

housing	:	Aluminium, hard-oxidized
measure spring	:	stainless steel 1.4310
diaphragm	:	NBR
knitted pressure wiring	:	C-steel / stainless steel

dimensions acc. to data-sheet : no. 229.898-07-X-001

Manufacturer : Dango & Dienenthal, Filbertechnik GmbH
57072 Siegen, C (0)271 / 401-0